



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	x Average		o Colder	o Warmer
Temperature application	x Medium (55°C)		o Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output</b>	<b>Prated</b>	<b>7</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>ηs</b>	<b>129</b>	<b>%</b>
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj = - 7°C	Pdh	6,3	kW	Tj = - 7°C	COPd	2,24	-
Degradation co-efficient	Cdh	1,0	-	Tj = + 2°C	COPd	3,18	-
Tj = + 2°C	Pdh	4,1	kW	Tj = + 7°C	COPd	4,26	-
Degradation co-efficient	Cdh	1,0	-	Tj = + 12°C	COPd	5,93	-
Tj = + 7°C	Pdh	4,3	kW	Tj = bivalent temperature	COPd	2,24	-
Degradation co-efficient	Cdh	1,0	-	Tj = operation limit temperature	COPd	1,79	-
Tj = + 12°C	Pdh	5,0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient	Cdh	1,0	-	Operation limit temperature	TOL	- 10	°C
Tj = bivalent temperature	Pdh	6,3	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	6,3	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	- 7	°C				
Cycling interval capacity for heating	Pcych	-	kW				

Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,025	kW	Rated heat output	Psup	0,7	kW
Thermostat-off mode	PTO	0,025	kW	Type of energy input	Electrical		
Standby mode	PSB	0,025	kW				
Crankcase heater mode	PCK	0,025	kW				

Other items							
Capacity control	variable			Rated air flow rate, outdoors	-		3200 m3/h
Sound power level, indoors/ outdoors	LWA	42/67	dB	Rated brine or water flow rate, outdoor heat exchanger	-		
Annual energy consumption	QHE	4371	kWh		-		

Contact details	<b>Fondital S.p.A</b> <b>Via Cerreto 40, 25079 Vobarno (BS) - Italy</b>		
-----------------	--	--	--



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	o Average		x Colder	o Warmer
Temperature application	x Medium (55°C)		o Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
<b>Rated heat output</b>	<b>Prated</b>	<b>7</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>ηs</b>	<b>112</b>	<b>%</b>	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj								
Tj = - 7°C	Pdh	4,6	kW	Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj				
Degradation co-efficient	Cdh	1,0	-	Tj = - 7°C	COPd	2,64	-	
Tj = + 2°C	Pdh	3,3	kW	Tj = + 2°C	COPd	3,24	-	
Degradation co-efficient	Cdh	1,0	-	Tj = + 7°C	COPd	4,76	-	
Tj = + 7°C	Pdh	4,2	kW	Tj = + 12°C	COPd	5,86	-	
Degradation co-efficient	Cdh	1,0	-	Tj = bivalent temperature	COPd	1,77	-	
Tj = + 12°C	Pdh	4,7	kW	Tj = operation limit temperature	COPd	1,26	-	
Degradation co-efficient	Cdh	1,0	-	Tj = - 15 °C (if TOL < - 20 °C)	COPd	1,77	-	
Tj = bivalent temperature	Pdh	5,9	kW	Operation limit temperature	TOL	- 22	°C	
Tj = operation limit temperature	Pdh	2,9	kW	Cycling interval efficiency	COPcyc	-	-	
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	5,9	kW	Heating water operating limit temperature	WTOL	60	°C	
Bivalent temperature	Tbiv	- 15	°C					
Cycling interval capacity for heating	Pcych	-	kW					

Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,025	kW	Rated heat output	Psup	4,1	kW
Thermostat-off mode	PTO	0,025	kW	Type of energy input	Electrical		
Standby mode	PSB	0,025	kW				
Crankcase heater mode	PCK	0,025	kWh				

Other items				Other items			
Capacity control	variable			Rated air flow rate, outdoors	-	3200	m3/h
Sound power level, indoors/ outdoors	LWA	42/67	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m3/h
Annual energy consumption	QHE	5982	kWh				

Contact details	Fondital S.p.A Via Cerreto 40, 25079 Vobarno (BS) - Italy
-----------------	--



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	o Average		o Colder	x Warmer
Temperature application	x Medium (55°C)		o Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output</b>	<b>P<sub>rated</sub></b>	<b>8</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>η<sub>s</sub></b>	<b>159</b>	<b>%</b>
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = - 7°C	Pdh	-	kW	T <sub>j</sub> = - 7°C	COPd	-	-
Degradation co-efficient	Cdh	-	-	T <sub>j</sub> = + 2°C	COPd	2,52	-
T <sub>j</sub> = + 2°C	Pdh	8,1	kW	T <sub>j</sub> = + 7°C	COPd	3,38	-
Degradation co-efficient	Cdh	1,0	-	T <sub>j</sub> = + 12°C	COPd	5,42	-
T <sub>j</sub> = + 7°C	Pdh	5,3	kW	T <sub>j</sub> = bivalent temperature	COPd	2,52	-
Degradation co-efficient	Cdh	1,0	-	T <sub>j</sub> = operation limit temperature	COPd	2,52	-
T <sub>j</sub> = + 12°C	Pdh	5,2	kW	T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient	Cdh	1,0	-	Operation limit temperature	TOL	2	°C
T <sub>j</sub> = bivalent temperature	Pdh	8,1	kW	Cycling interval efficiency	COPcyc	-	-
T <sub>j</sub> = operation limit temperature	Pdh	8,1	kW	Heating water operating limit temperature	WTOL	60	°C
T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Cycling interval capacity for heating	Pcych	-	kW				

Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	0,0	kW
Thermostat-off mode	P <sub>TO</sub>	0,025	kW	Type of energy input	Electrical		
Standby mode	P <sub>SB</sub>	0,025	kW				
Crankcase heater mode	P <sub>CCK</sub>	0,025	kW				

Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	3200	m <sup>3</sup> /h
Sound power level, indoors/ outdoors	LWA	42/67	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h
Annual energy consumption	QHE	2645	kWh				

Contact details	<b>Fondital S.p.A</b> <b>Via Cerreto 40, 25079 Vobarno (BS) - Italy</b>		
-----------------	--	--	--



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	x Average		o Colder	o Warmer
Temperature application	o Medium (55°C)		x Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output</b>	<b>Prated</b>	<b>7</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>ηs</b>	<b>181</b>	<b>%</b>
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj = - 7°C	Pdh	6,2	kW	Tj = - 7°C	COPd	2,94	-
Degradation co-efficient	Cdh	1,0	-	Tj = + 2°C	COPd	4,39	-
Tj = + 2°C	Pdh	3,9	kW	Tj = + 7°C	COPd	6,29	-
Degradation co-efficient	Cdh	1,0	-	Tj = + 12°C	COPd	8,43	-
Tj = + 7°C	Pdh	3,0	kW	Tj = bivalent temperature	COPd	2,94	-
Degradation co-efficient	Cdh	1,0	-	Tj = operation limit temperature	COPd	2,69	-
Tj = + 12°C	Pdh	3,6	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient	Cdh	0,9	-	Operation limit temperature	TOL	- 10	°C
Tj = bivalent temperature	Pdh	6,2	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	5,9	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	- 7	°C				
Cycling interval capacity for heating	Pcych	-	kW				

Power consumption in modes other than active mode				Supplementary heater			
Off mode				Rated heat output			
Thermostat-off mode				Psup			
Standby mode				1,1			
Crankcase heater mode				kW			
				Type of energy input			
				Electrical			

Other items			
Capacity control	variable		
Sound power level, indoors/ outdoors	LWA	42/67	dB
Annual energy consumption	QHE	3149	kWh
Rated air flow rate, outdoors	-	3200	m3/h
Rated brine or water flow rate, outdoor heat exchanger	-	-	m3/h

Contact details	Fondital S.p.A Via Cerreto 40, 25079 Vobarno (BS) - Italy
-----------------	--



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	o Average		x Colder	o Warmer
Temperature application	o Medium (55°C)		x Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit			
<b>Rated heat output</b>	<b>Prated</b>	<b>7</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>ηs</b>	<b>146</b>	<b>%</b>			
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj										
Tj = - 7°C	Pdh	4,5	kW	Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj						
Degradation co-efficient	Cdh	1,0	-	Tj = - 7°C	COPd	3,26	-			
Tj = + 2°C	Pdh	3,3	kW	Tj = + 2°C	COPd	4,26	-			
Degradation co-efficient	Cdh	1,0	-	Tj = + 7°C	COPd	6,04	-			
Tj = + 7°C	Pdh	4,3	kW	Tj = + 12°C	COPd	7,26	-			
Degradation co-efficient	Cdh	1,0	-	Tj = bivalent temperature	COPd	2,63	-			
Tj = + 12°C	Pdh	4,9	kW	Tj = operation limit temperature	COPd	1,52	-			
Degradation co-efficient	Cdh	1,0	-	Tj = - 15 °C (if TOL < - 20 °C)	COPd	2,63	-			
Tj = bivalent temperature	Pdh	5,8	kW	Operation limit temperature	TOL	- 22	°C			
Tj = operation limit temperature	Pdh	4,5	kW	Cycling interval efficiency	COPcyc	-	-			
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	5,8	kW	Heating water operating limit temperature	WTOL	60	°C			
Bivalent temperature	Tbiv	- 15	°C							
Cycling interval capacity for heating	Pcych	-	kW							

Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,025	kW	Rated heat output	Psup	2,5	kW
Thermostat-off mode	PTO	0,025	kW	Type of energy input	Electrical		
Standby mode	PSB	0,025	kW				
Crankcase heater mode	PCK	0,025	kWh				

Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	3200	m3/h
Sound power level, indoors/ outdoors	LWA	42/67	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m3/h
Annual energy consumption	QHE	4628	kWh				

Contact details	<b>Fondital S.p.A</b> <b>Via Cerreto 40, 25079 Vobarno (BS) - Italy</b>		
-----------------	--	--	--



## Technical parameters for heat pump space heaters and heat pump combination heaters

COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters. ANNEX II, point 5, Table 2.

COMMISSION DELEGATED REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device. ANNEX V, Table 8.

Model(s)		PROCIDA AWS X8 (PROCIDA AWS 8 (O) + PROCIDA IWU 8)		
Air-to-water heat pump	x Yes	o No		
Water-to-water heat pump	o Yes	x No		
Brine-to-water heat pump	o Yes	x No		
Low-temperature heat pump	o Yes	x No		
Equipped with a supplementary heater	x Yes	o No		
Heat pump combination heater	o Yes	x No		
Climate conditions	o Average		o Colder	x Warmer
Temperature application	o Medium (55°C)		x Low (35°C)	
Applied Standards	EN14825			

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output</b>	<b>Prated</b>	<b>8</b>	<b>kW</b>	<b>Seasonal space heating energy efficiency</b>	<b>ηs</b>	<b>217</b>	<b>%</b>
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	-	kW	Tj = - 7°C	COPd	-	-
Degradation co-efficient	Cdh	-	-	Tj = + 2°C	COPd	3,58	-
Tj = + 2°C	Pdh	8,2	kW	Tj = + 7°C	COPd	4,84	-
Degradation co-efficient	Cdh	1,0	-	Tj = + 12°C	COPd	7,08	-
Tj = + 7°C	Pdh	5,4	kW	Tj = bivalent temperature	COPd	3,58	-
Degradation co-efficient	Cdh	1,0	-	Tj = operation limit temperature	COPd	3,58	-
Tj = + 12°C	Pdh	5,1	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient	Cdh	1,0	-	Operation limit temperature	TOL	2	°C
Tj = bivalent temperature	Pdh	8,2	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	8,2	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Cycling interval capacity for heating	Pcych	-	kW				

Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,025	kW	Rated heat output	Psup	0,0	kW
Thermostat-off mode	PTO	0,025	kW	Type of energy input	Electrical		
Standby mode	PSB	0,025	kW				
Crankcase heater mode	PCK	0,025	kW				

Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	3200	m3/h
Sound power level, indoors/ outdoors	LWA	42/67	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m3/h
Annual energy consumption	QHE	1947	kWh				

Contact details	<b>Fondital S.p.A</b> <b>Via Cerreto 40, 25079 Vobarno (BS) - Italy</b>		
-----------------	--	--	--